

LUBRICHEM Syn FMG 220

Synthetic and food grade gear oil

Description

LUBRICHEM Syn FMG is a range of fully synthetic food grade gear oils mainly suitable for the lubrication of drive chains, conveyor chains, gearboxes and reduction units. LUBRICHEM Syn FMG oils contain special additives that extend relubrication intervals.

LUBRICHEM Syn FMG is NSF H1 registered for incidental food contact.

Applications

LUBRICHEM Syn FMG oils are developed for the lubrication of gears and gearboxes, conical and helical gears, bearing, screws and joints, and can be used in most applications in the manufacturing process in the food production and processing industry thanks to its great performance characteristics and carefully chosen additives.

LUBRICHEM Syn FMG is also suitable for chain lubrication:

- Penetrates to links and pins reducing wear and extending chain life
- Adhesive additives ensure non-drip, no fling thus providing lasting lubrication
- Excellent adhesive characteristics ensures a high degree of water resistance and protects parts from corrosion even in the presence of alkali materials commonly associated with the food industry

Extremely wide temperature range ensures maximum application versatility

Benefits

- Extremely good oxidation stability which extends lubricant life
- Unaffected by water – demulsibility ensures total separation of water from oil

LUBRICHEM

Adhesive additives coat gears and provide anti-wear protection at start-up

- Synthetic oil with HVI ensures reduced viscosity change with temperature increase

Typical performance data

	Syn FMG 220
Kin. viscosity @ 40°C, cSt	220
Kin. viscosity @ 100°C, cSt	25
Viscosity index	> 140
Flash point, °C	> 260
Pour point, °C	<-45
FZG, stage	12+
NSF approval, H1	159189

HEALTH / SAFETY

For information about safe handling and use of this product, refer to the Material Safety Data Sheet